

Learn More

Everest Printer Specifications

Item	Description
Printing Speed (including tray cycle time)	60 seconds or less for CMY color coverage. 66 seconds for CMY+W First print is 5 minutes, which includes warm-up time.
Printing Modes	Monochrome, CMY, and CMY+W
Print Quality	Equivalent of 300 DPI (dots per inch) using variable dot technology
Media Types	CDs or DVDs with Everest-compatible coating
Ribbons	Monochrome (Black) CMY (Cyan, Magenta, and Yellow) CMY+W (Cyan, Magenta, Yellow, and White)
Ribbon Capacity	Retransfer Ribbon = 1000 discs or 500 discs Black Ribbon = 1000 discs CMY Ribbon = 500 discs CMY+W Ribbon = 375 discs
Physical Properties	9.7" H x 9.4" W x 14.8" D (24.6 cm x 24.0 cm x 37.5 cm) Depth with print tray extended – 22.25" (56.5 cm) Left side cover open for print ribbon replacement – add additional 9.1" (23 cm) Weight: 40.8 lbs (18.5 Kg) Weight with packaging: 50.7 lbs (23Kg)
Interface	USB 2 (Universal Serial Bus) – B type connector
Power	100 – 120V 500W / 220 – 240V 500W 50 / 60 Hz (manual switching)
Operating Temperature	59° F to 86° F (15° C to 30° C)
Relative Humidity	30% to 70% non-condensing
Minimum System Requirements	<p>Windows-based PC</p> <ul style="list-style-type: none"> Pentium 300 or better with 128MB RAM Windows 2000 Professional or XP Professional USB port <p>Macintosh computer</p> <ul style="list-style-type: none"> G3 or better with 128 MB RAM Macintosh OS X version 10.3/10.4 USB port