



TRIVIEW

Preliminary Spec Sheet

20" Premium Series

Closed Circuit TV Monitor

MODEL TLM-2001

Panel Type	20.1 inch
Viewable Size	408mm (H) x 306mm(V)
Dot Pitch	0.51mm x 0.51mm
View Angle (h/v)	-80°, +80°/-60°, +80°
Contrast Ratio	700:1
Brightness	450 cd/m ²
Resolution	800 x 600
Response Time	16ms (tr:4ms, tf:12ms)
Display Colors	16.2 million
Control key define	Channel, Menu, Up, Down, Left, Right, Power
Power Supply	
Input-Voltage	100~240VAC
Consumption	<55W
VIDEO	
Input	Composite video, connector: 2 BNCS-video, connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω
Output	2 BNC connector for CVBS loop-through output
OSD	Contrast, Brightness, Color, Tint, Language, OSD setting, Color Temperature select, Volume, PIP, Recall, Exit
System	
Compatibility	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz
Analog VGA	
Input	Analog RGB: 0.707Vp-p / 75Ω, Connector: DVH (with converting cable)
OSD	OSD Contrast, Brightness, Phase, Clock, H Position, V Position, Auto Adjust, OSD setting, Color Temperature select, Volume, PIP, Recall, Exit
Plug & Play	DDC2B
power Management	VESA DPMS
Support Timing	VESA VGA / SVGA / XGA
Audio	
Input	Connector: 2 x RCA jack (L+R) Level: 1.0Vp-p / 1 KHz
Output	Connector: 2 x RCA jack (L+R)
Speaker	1W x 2 embedded
Dimensions	18.5"(w) x 15.0"(h) x 4.3"(d) 461mm(w) x 380.5mm(h) x 110mm (d)
Additional benefits	3D comb filter De-interlaced PIP/VOV RoHS compliant